



DENHOLM MACNAMEE LIMITED
PLANT HIRE DIVISION

Greenbank Place, East Tullos Industrial Estate, Aberdeen AB12 3BT
Telephone: +44 (0)1224 248600

BJV Jetting Nozzle

Self Rotating Jetting Head

Powerful, versatile jet angles, eliminate manual twisting of the fixed-jet nozzle.
Can be self-propelled by using stronger back jets.
Controlled rotation for maximum jet power.
Easy to maintain, no leak seal.



BJV Jetting Head

Applications

- | | |
|----------------------------|----------------|
| 1 Pipelines | 1 Stacks |
| 1 Tank or Vessel interiors | 1 Well screens |
| 1 Asbestos removal | 1 Ducts |
| 1 Refractory removal | 1 Boilers |
| 1 Coker tubes | 1 Furnaces |

Specifications - BJV

	BJV Standard	BJV-M
Max Pressure	15,000 psi	15,000 psi
Rotation Speed		
Fast	50-250 rpm	40-200 rpm
Slow	10-100 rpm	5-80 rpm
Flow Capacity	60 gpm 230 l/min	100 gpm 380 l/m
Flow Rating, Cv	2.3	4.6m
Inlet Port	3/4 npt	3/4 npt



BJV Head, Centralizer & Extension Arms